5700/5800 SERIES

PRESSURE WASHERS / SINCE 1970

FEATURES

8.0 to 9.5 GPM @ 2500 to 3000 PSI
Stainless Steel Coil Skin
20 HP

HOT WATER | **ELECTRIC** | **BELT DRIVE**

Upright, vertical coil delivers high efficiency and maintains constant temperature using oil, natural gas or liquid propane.

Controls for the pump, burner and detergent are easily accessible.

Remote ready for operation in wash bays.

Adjustable upstream detergent injection ensures high-pressure sudsing for better cleaning.

Stainless steel coil skin provides extra durability to withstand overspray.

Elevated gas valve protects valve from water damage, and is located at the back corner for easy installation and service.

Burner assembly pivots down to allow access to burner ring and pilot assembly for maintenance.

Insulated Hotsy trigger gun and insulated wand with ergonomic, adjustable side handle.

Pressure relief valve protects the machine and user from thermal expansion.

Control panel provides access to the main controls. Remove the front panel to access the Smart Relay for secured control of desired operating settings, such as auto start/stop functionality.

Sleek side and front panels are easily removed for routine maintenance and service access.

50-ft. length of high-pressure hose for easy maneuverability around a large working area.

With its 20 HP motor driving the incomparable Hotsy Triplex Pump and a vertical banded belt, the 5700 and 5800 Series delivers cleaning power up to 9.5 GPM and 3000 PSI.

Quick disconnect stainless steel nozzles are color coded for quick changing between 0°, 15°, 40° spray nozzles.



Motor is mounted to slide out rails for easy removal.

Programmable Smart Control Automation provides complete control over the machine's run time, auto start/stop and time delay shut down functionality.

Large frame Hotsy belt-drive pump features NESTechnology with U-Seals for 3 times longer pump life.

OPTIONS FOR 5700/5800 SERIES

12" Power Dampener
Remote Station (1)
R-Con Wireless Remote Kit (2)
Wall Mount Remote Kite (3)
LP Conversion Kit
12" Natural Gas- or LP Gas-Fired Draft Diverter
Soap Solenoid and Switch
Water Inlet Solenoid

1

2

3

5700/5800 SERIES

Hot-Water **ELECTRIC** Models

POWERFUL MODELS FOR TOUGH INDUSTRIAL CLEANING..

■ **Oil, NG or LP-Fired** ■ **8 to 9.5 GPM @ 2500 to 3000 PSI** ■ **20 HP**

MODEL	PART NO.	GPM	PSI	HP	VOLT/PH	AMPS	FUEL	BTU/HR	PUMP MODEL	HOSE (FT)	DIMENSIONS (LXWXH)	SHIP WT (LBS)
5730SS	1.109-658.0	8.0	3000	20	230/3	44	Oil*	768,000	HX9536L.2	50	51"x31"x63.4"	1,471
5732SS-208	1.109-654.0	8.0	3000	20	208/3	55	NG	720,450	HX9536L.2	50	51"x31"x63.4"	1,471
5732SS	1.109-655.0	8.0	3000	20	230/3	42	NG	720,450	HX9536L.2	50	51"x31"x63.4"	1,471
5733SS	1.109-659.0	8.0	3000	20	460/3	23	Oil*	768,000	HX9536L.2	50	51"x31"x63.4"	1,471
5735SS	1.109-656.0	8.0	3000	20	460/3	21	NG	720,450	HX9536L.2	50	51"x31"x63.4"	1,471
5736SS	1.109-657.0	8.0	3000	20	575/3	16	NG	720,450	HX9536L.2	50	51"x31"x63.4"	1,471
5832SS	1.109-651.0	9.5	2500	20	230/3	42	NG	939,890	HX1036L.2	50	51"x31"x63.4"	1,471
5832SS-208	1.109-650.0	9.5	2500	20	208/3	48	NG	939,890	HX1036L.2	50	51"x31"x63.4"	1,471
5835SS	1.109-652.0	9.5	2500	20	460/3	21	NG	939,890	HX1036L.2	50	51"x31"x63.4"	1,461
5836SS	1.109-653.0	9.5	2500	20	575/3	16	NG	939,890	HX1036L.2	50	51"x31"x63.4"	1,471

**Oil-fired models are not supplied with a fuel tank*

DETERGENTS

To clean like a pro, you need to include detergents. Hotsy offers a full line of detergents for cleaning grease, dirt, road grime, aluminum, sanitation and so much more. Our detergents help you clean faster and save money.

PARTS & ACCESSORIES



Clean faster and more efficiently with pressure washer accessories like flat surface cleaners and turbo nozzles.

SERVICE

Hotsy factory-trained technicians keep your equipment running with on-site or in shop maintenance and tune-ups. Plus, we repair all brands.

The Pressure Washer The Pros Use.

EST. 1970

HOTSY.COM

Tel: 800.525.1976

Fax: 888.880.9631

Email: info@hotsy.com

Distributed by:

NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We meet the CETA testing specs for machine performance at +_10% and in some cases are tighter within +_ 5% of listed specifications.

Specifications & product descriptions subject to change without notice. Hotsy's manufacturing facilities have established and apply a quality and environmental management system to be ISO 9001:2008 and ISO 14001:2001 certified.

VISIT US ONLINE

Facebook/Instagram HotsyCleaningSystems

LinkedIn Hotsy-Corp

Twitter TheHotsyMan

YouTube HotsyCleaningSystems

Get Hotsy Email Bit.ly/GetHotsy

© 2023 Kärcher North America

P/N HOT_1800 Effective 07/23

CWC SERIES

PRESSURE WASHERS / SINCE 1970

FEATURES

4 - 5 GPM @ 2000 to 3000 PSI
230V, 1PH; 230V, 460V or 575V, 3PH

COLD WATER | **ELECTRIC** | **BELT DRIVE**

Ideal for the food industry since hot water can be used. Remote ready for operation in wash bays.

50-ft. high-pressure hose for easy maneuverability around a large working area

Locking lid prevents accidental removal of both panels around the belt and pulley

Insulated Hotsy trigger gun and insulated wand with ergonomic, side handle

Sleek side and front removeable panels provide easy access to the entire washer for service and maintenance

Adjustable upstream detergent injection ensures high-pressure sudsing for better cleaning

Hotsy-designed Triplex pumps carry a 7-year limited warranty

Float tank helps maintain constant water pressure and flow while helping to prevent sediment from entering the machine's components

Large frame Hotsy belt-drive pump features NESTechnology with U-Seals for 3 times longer pump life. The pump also has an oil drain, allowing for easy oil changes.

Vertical tensioned belt provides extended life and reduced maintenance costs by eliminating multiple belts that stretch at different rates.



Programmable Smart Control Automation provides complete control over the machine's run time, auto start/stop and time delay shutdown functionality.

OPTIONS FOR COLD WATER CABINET

R-Con Wireless Remote Kit (Image 1)

Remote Station (Image 2)

Soap Solenoid and Switch

1

2

Stainless Steel Cabinet is available on special order



CWC SERIES
Cold Water Cabinet

STATIONARY PRESSURE WASHER FOR HEAVY-DUTY CLEANING.
■ **Hotsy Triplex Pump with 7-yr Warranty** ■ **4.0 to 5.0 GPM @ 2000 to 3000 PSI** ■ **ETL-Certified for Safety**

MODEL	PART NO.	GPM	PSI	HP	MOTOR RPM	VOLT/PH	AMP	PUMP MODEL	HOSE (FT)	SHIP WT (LBS)
CWC-53	1.106-572.0	4.0	3000	7.5	1725	230/1	36	HM4030R.3	50	340
CWC-54	1.106-573.0	4.0	3000	7.5	1725	230/3	23	HM4030R.3	50	340
CWC-55	1.106-574.0	4.0	3000	7.5	1725	460/3	11	HM4030R.3	50	340
CWC-56	1.106-575.0	4.0	3000	7.5	1770	575/3	9	HM4030R.3	50	340
CWC-63	1.106-576.0	5.0	2000	7.5	1725	230/1	36	HM4035R.3	50	340
CWC-64	1.106-577.0	5.0	2000	7.5	1725	230/3	18	HM4035R.3	50	340
CWC-65	1.106-578.0	5.0	2000	7.5	1725	460/3	9	HM4035R.3	50	340
CWC-66	1.106-579.0	5.0	2000	7.5	1770	575/3	8	HM4035R.3	50	340

Dimensions: 24.5L x 21W x36H (inches)

DETERGENTS

To clean like a pro, you need to include detergents. Hotsy offers a full line of detergents for cleaning grease, dirt, road grime, aluminum, sanitation and so much more. Our detergents help you clean faster and save money.

PARTS & ACCESSORIES



Clean faster and more efficiently with pressure washer accessories like flat surface cleaners and turbo nozzles.

SERVICE

Hotsy factory-trained technicians keep your equipment running with on-site or in shop maintenance and tune-ups. Plus, we repair all brands.

hotsy®
The Pressure Washer The Pros Use.
EST. 1970

HOTSY.COM
Tel: 800.525.1976
Fax: 888.880.9631
Email: info@hotsy.com

Distributed by:

NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We meet the CETA testing specs for machine performance at +_10% and in some cases are tighter within +_ 5% of listed specifications.

Specifications & product descriptions subject to change without notice. Hotsy's manufacturing facilities have established and apply a quality and environmental management system to be ISO 9001:2008 and ISO 14001:2001 certified.

VISIT US ONLINE

Facebook/Instagram HotsyCleaningSystems
LinkedIn Hotsy-Corp
Twitter TheHotsyMan
YouTube HotsyCleaningSystems
Get Hotsy Email Bit.ly/GetHotsy

© 2021 Kärcher North America

P/N HOT_CWC Effective 07/23

GAS ENGINE
ROLL CAGE SERIES

PRESSURE WASHERS / SINCE 1970

FEATURES

2.7 - 4.0 GPM @ 2400 to 3500 PSI
12V DC Burners

HOT WATER | **OIL FIRED** | **BELT/DIRECT DRIVE**

Model 965SS:
Oil Fired, 3.0 GPM
@ 3000 PSI

Hotsy-designed triplex direct-drive pump carries a 7-year warranty

12" heavy-duty **flat free tires**

50-ft wire-braided high pressure hose with swivel on one end

Trigger gun control with cool-grip

Heavy-duty regulator rectifier eliminates the need for battery

Stainless-steel coil skin provides extra durability and resists corrosion

Oil-fired Wayne **burner**

Lifting eyes let power equipment do the hoisting

8-gallon, removable, rust-proof polyethylene fuel tank has fuel gauge in cap

Protective Heavy-duty roll-cage chassis

Control box with adjustable temperature control, hour meter and burner on/off switch

Upstream detergent injection

Model 1075BE Compact:
4.0 GPM@ 3500 PSI; Vanguard 400 engine; 12V DC water heater (12V battery required, not supplied)

MODEL	PART NO.	GPM	PSI	ENGINE	CCS	BURNER	BTU/HR	PUMP MODEL	DIMENSIONS (LXWXH)	SHIP WT (LBS)
871SS*	1.110-014.0	2.7	2400	Honda GX200	196	12V DC	248,500	HPP3035G	43"x27"x39"	410
965SSE CAL†	1.110-090.0	3.0	3000	Vanguard 400	408	12V DC	248,500	HPP3035G.1	47"x31"x41"	445
1065SSE CAL†	1.110-089.0	3.5	3000	Vanguard 400	408	12V DC	309,900	HS3540G.3	47"x31"x45"	510
1075SSE†	1.110-012.0	4.0	3500	Honda GX390	389	12V DC	309,900	HS4040G.3	47"x31"x45"	520
1075SSE CAL†	1.110-080.0	4.0	3500	Vanguard 400	408	12V DC	309,900	HS4040G.3	47"x31"x45"	520
1075BE Compact†	1.110-088.0	4.0	3500	Vanguard 400	408	12V DC	309,900	HM4035R.3	47"x31"x45"	520
1075BE Compact†	1.110-099.0	4.0	3500	Honda GX390	389	12V DC	309,900	HM4035R.3	47"x31"x45"	520

*Battery not required † 12V battery required, but not supplied E = Electric-start engine B=Belt

WARNING: This product can expose you to chemicals including Lead and Diisononyl Phthalate, which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

HOTSY.COM NOTHING CLEANS LIKE A **HOTSY!**

NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models, and subject to change without notice. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We meet the CETA testing specs for machine performance at +_10% and in some cases are tighter within +_ 5% of listed specifications.

Hotsy's manufacturing facilities have established and apply a quality and environmental management system to be ISO 9001:2008 and ISO 14001:2001 certified.

© 2025 Kärcher North America
P/N HOT_GasEngineRollCage Effective 03/25

Distributed by:

HSS & HSDS
SUPERSKID SERIES

PRESSURE WASHERS / SINCE 1970

FEATURES

5.0 to 9.5 GPM @ 2500 to 3500 PSI
Stainless Steel
Coil Wrap
Electric Start

HOT WATER | **DIESEL** | **BELT DRIVE**

Upright, diesel-fired burner with stainless-steel coil skin is highly efficient and maintains constant hot water using diesel fuel

3/4-inch schedule 80 heating coil is wrapped with a thick foil backed blanket insulation, carrying a 5-year non pro-rated warranty

Removable frame supports for easy service access

Rugged square tube frame protects machine's vital components

Fuel/water separator prolongs fuel pump life

High efficiency **Wayne 12VDC Burner** with proprietary controller

50-ft. of two-wire, heavy-duty abrasion resistant **hose**

Heavy-duty trigger gun and wand with insulated cool grips

Hotsy triplex, tri-banded belt drive, positive-displacement pump carries a 7-year warranty

HSDS models offer super duty **Hawk pump** with lower pump RPMs for long lasting durability

Tier IV Kubota Diesel engine in 16 or 24 HPOperate longer with two diesel crossedlinked HDPE tanks, 25 gallons each

Optional large float tank maintains constant pressure and flow while preventing sediment from entering the machine's components

Ready plumbed for connection to remote water tank

High flow VRT100 unloader handles 27 GPM @ 5075 PSI

Water resistant control panel includes adjustable temperature control, heavy-duty heater switch, hour meter, volt meter, keyed ignition switch, and nozzle storage

Optional adjustable **high-pressure detergent kit** (included with the float tank kit)

Optional steam combination control

Safety relief valve protects machine and user

Pump size comparison:
The HFR and HHP pumps from Leuco used in the Super Duty models dwarf the standard HX.

OPTIONS FOR HSS/HSDS SERIES

Dual Gun Kit - includes necessary fittings, extra hose gun and wand

Steam Kit - includes necessary fittings and panel mount control valve

Float Tank Kit - includes float tank, necessary fittings and panel mount detergent metering valve

SUPER SKID HSS SERIES

Hot-Water **DIESEL** Belt Drive Models

POWERFUL MODELS FOR TOUGH INDUSTRIAL CLEANING.

■ **Gas/Diesel-Powered** ■ **4.5 to 8.0 GPM @ 3000 to 4000 PSI** ■ **Electric Start**

MODEL	PART NO.	GPM	PSI	ENGINE MODEL	CCs	BURNER	BTU/HR	PUMP MODEL	HOSE	DIMENSIONS (LXWXH)	SHIP WT (LBs)
HSS-503069E	1.110-604.0	5.0	3000	Kubota Z602-E4B	599	12V DC	465,000	HX5843R.2	50'-3/8"	73"x37"x64"	1305
HSS-653569E	1.110-605.0	6.5	3500	Kubota D1105-E4B	1123	12V DC	565,000	HX8043R.2	50'-3/8"	73"x37"x64"	1710
HSS-803069E	1.110-606.0	8.0	3000	Kubota D1105-E4B	1123	12V DC	635,000	HX9536.2	50'-1/2"	73"x37"x64"	1715
HSS-952569E	1.110-607.0	9.5	2500	Kubota D1105-E4B	1123	12V DC	780,000	HX1036R.2	50'-1/2"	73"x37"x64"	1715

MODEL	PART NO.	GPM	PSI	ENGINE MODEL	CCs	BURNER	BTU/HR	PUMP MODEL	HOSE	DIMENSIONS (LXWXH)	SHIP WT (LBs)
HSDS-503069E	1.110-616.0	5.0	3000	Kubota Z602-E4B	599	12V DC	465,000	HHP2750R	50'-3/8"	73"x37"x64"	1610
HSDS-653569E	1.110-617.0	6.5	3500	Kubota D1105-E4B	1123	12V DC	565,000	HHP3650R	50'-3/8"	73"x37"x64"	2005
HSDS-803069E	1.110-618.0	8.0	3000	Kubota D1105-E4B	1123	12V DC	635,000	HFR40FR	50'-1/2"	73"x37"x64"	2015
HSDS-952569E	1.110-619.0	9.5	2500	Kubota D1105-E4B	1123	12V DC	780,000	HFR60FR	50'-1/2"	73"x37"x64"	2020

All models are Electric Start. 12V battery required for all models, but not supplied

DETERGENTS

To clean like a pro, you need to include detergents. Hotsy offers a full line of detergents for cleaning grease, dirt, road grime, aluminum, sanitation and so much more. Our detergents help you clean faster and save money.

PARTS & ACCESSORIES



Clean faster and more efficiently with pressure washer accessories like flat surface cleaners and turbo nozzles.

SERVICE

Hotsy factory-trained technicians keep your equipment running with on-site or in shop maintenance and tune-ups. Plus, we repair all brands.

NOTHING CLEANS LIKE A HOTSY!

EST. 1970

HOTSY.COM

Tel: 800.525.1976

Email: info@hotsy.com

Distributed by:

NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We meet the CETA testing specs for machine performance at +_10% and in some cases are tighter within +_ 5% of listed specifications.

Specifications & product descriptions subject to change without notice. Hotsy's manufacturing facilities have established and apply a quality and environmental management system to be ISO 9001:2008 and ISO 14001:2001 certified.

VISIT US ONLINE

Facebook/Instagram HotsyCleaningSystems

LinkedIn Hotsy-Corp

Twitter TheHotsyMan

YouTube HotsyCleaningSystems

Get Hotsy Email Bit.ly/GetHotsy

© 2021 Kärcher North America

P/N HOT_HSS Effective 06/21

HWE SERIES
ALL-ELECTRIC

PRESSURE WASHERS / SINCE 1970

FEATURES

3.5 to 4.0 GPM @ 2000 to 3000 PSI
Auto Start/Stop

HOT WATER | **ALL-ELECTRIC** | **BELT DRIVE**

Magnetic Motor Starter for long life of reliable starting.

Mounted on a **Power Platform** with four vibration isolators to minimize shaking and stress on the frame.

The **Auto Start** function allows the unit to be turned on with the pull of the trigger for convenient remote operation.

Inlet Filter strainer protects pump from debris.

50 ft. **High Pressure Hose** rated for up to 5000 PSI with Insulated, fatigue-free Trigger Gun and stainless steel, dual-lance **Variable Pressure Wand.**

Three quick-coupler **Nozzles** are made of hardened stainless steel and mounted for ready access.

Heavy-duty **Upper and Lower Cabinet** is protected by an epoxy powder coat finish.

Safety **Low-Water Float Switch** protects heating elements from burn out due to lack of water.

Easy-to-attach **Detergent Injector** for easy soap application.

Contains nine high-efficiency **Heating Elements** that do not come in contact with the pressurized water, resulting in reduced scale build up, lower maintenance, and longer life.

Hotsy-designed **Triplex Pumps** carry a 7-year limited warranty and **Heater Coil** carries a 5-year warranty.

OPTIONS FOR HWE SERIES

Stainless Steel Washer Wrap

Option, Time Delay Shut Down

California Air Resources Board Verified

MODEL	PART NO.	GPM	PSI	HP	MOTOR	AMPS	VOLT/PH	KvA HOUR	PUMP MODEL	PORTABILITY	DIM (LXWXH)	SHIP WT (LBS)
HWE-402009C	1.109-646.0	4.0	2000	6.2	Baldor	55	460/3	40.5	138,308	HM4030R.3	34"x25"x52"	620
HWE-403009C	1.109-647.0	3.5	3000	7.5	WEG	59	460/3	40.5	138,308	HM4030R.3	34"x25"x52"	640
HWE-402009F	1.109-958.0	3.5	2000	5	Baldor	46	575/3	40.5	138,308	HM4030R.3	34"x25"x52"	620
HWE-403009F	1.109-959.0	3.5	3000	7.5	Baldor	49	575/3	40.5	138,308	HM4030R.3	34"x25"x52"	640

WARNING: This product can expose you to chemicals including Lead and Diisononyl Phthalate, which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

NOTHING CLEANS LIKE A HOTSY.
EST. 1970

HOTSY.COM
Tel: 800.525.1976
Email: info@hotsy.com

Distributed by:

NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We meet the CETA testing specs for machine performance at +_10% and in some cases are tighter within +_ 5% of listed specifications.

Specifications & product descriptions subject to change without notice. Hotsy's manufacturing facilities have established and apply a quality and environmental management system to be ISO 9001:2008 and ISO 14001:2001 certified.

VISIT US ONLINE

Facebook/Instagram HotsyCleaningSystems
LinkedIn Hotsy-Corp
Twitter TheHotsyMan
YouTube HotsyCleaningSystems
Get Hotsy Email Bit.ly/GetHotsy

© 2025 Kärcher North America

P/N HOT_HWE Effective 08/25